

SUBDIVISION OF T. 40 N., R. 43 E.

CHAINS

T40N R43E

$$\frac{1}{4} \begin{array}{r} \text{S } 6 \\ \text{S } 7 \end{array}$$

1965

raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor.

46.00 Wash, 20 lks. wide, 2 ft. deep, drains N.

79.98 The cor. of secs. 5, 6, 7 and 8.

Land, gently rolling.
Soil, sandy clay loam.
Undergrowth, sagebrush.

N. 0° 01' E., bet. secs. 5 and 6.

Over gently rolling land, through medium undergrowth.

40.00 Point for the ¼ sec. cor. of secs. 5 and 6.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T40N R43E

$$\frac{1}{4} \begin{array}{r} \text{S } 6 \mid \text{S } 5 \\ 1965 \end{array}$$

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

41.50 Wash, 30 lks. wide, 4 ft. deep, drains NW.

57.60 Bladed dirt road, bears SE. and NW.

62.58 Intersect the Eighth Standard Parallel North.

Point for the closing cor. of secs. 5 and 6.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T41N R43E

$$\begin{array}{r} \text{S } 31 \\ \text{S } 6 \mid \text{S } 5 \end{array}$$

CC

T40N

1965

raise a mound of stone, 2½ ft. base, 1½ ft. high, S. of cor.

from this corner

The standard ¼ sec. cor. of sec. 31, T. 41 N., R. 43 E., bears S. 88° 56' W., 0.25 chs. dist.

The standard cor. of secs. 31 and 32, T. 41 N., R. 43 E., bears N. 88° 56' E., 40.18 chs. dist.

Land, gently rolling.
Soil, sandy clay loam.
Undergrowth, sagebrush and shadscale.