

SUBDIVISION OF T. 40 N., R. 43 E.

CHAINS	
53.30	Small wash, drains SSW.
56.70	Ravine, drains SW.; asc. 60 ft. over a W. slope.
61.00	Low ridge, bears NE. and SW.; desc. 20 ft. along a N. slope.
71.10	Small wash, drains N.; asc. 30 ft. over a W. slope.
76.00	Spur, slopes N.; desc. 10 ft. over an E. slope.
80.00	The cor. of secs. 3, 4, 9 and 10. Land, rolling. Soil, sandy clay loam. Undergrowth, sagebrush.
	N. 0° 02' E., bet. secs. 3 and 4. Over a rolling NNE. slope, through medium undergrowth; desc. 90 ft.
38.60	Wash, 15 lks. wide, 3 ft. deep, drains W.; asc. 20 ft. over a S. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. T40N R43E $\frac{1}{4}$ S 4 S 3 1965 raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. Asc. 30 ft. over a S. slope.
41.30	Begin descent over a gently rolling N. slope; desc. 40 ft.
62.90	Intersect the Eighth Standard Parallel North. Point for the closing cor. of secs. 3 and 4. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. T41N R43E S 33 S 4 S 3 CC T40N 1965 raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, S. of cor. from this corner The standard $\frac{1}{4}$ sec. cor. of sec. 33, T. 41 N., R. 43 E., heretofore described, bears S. 89° 58' E., 1.22