CHAINS	
	asc. 20 ft. over a S. slope.
3.20	Slope changes to SW. slope; asc. 30 ft.
12.30	Begin descent of 60 ft. over a gradual N. slope.
40.00	Point for the ¼ sec. cor. of secs. 2 and 3.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T40N R43E
¼
S 3 | S 2
1965

raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.

Desc. 60 ft. over a gradual N. slope.

62.85 Intersect the Eighth Standard Parallel North.

Point for the closing cor. of secs. 2 and 3.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T41N R43E
S 34
S 3 | S 2
CC
T40N
1965

raise a mound of stone, 3 ft. base, 2½ ft. high, S. of cor.

from this corner

The standard ¼ sec. cor. of sec. 34, T. 41 N., R. 43 E., heretofore described, bears S. 89° 58' E., 2.01 chs. dist.

The standard cor. of secs. 33 and 34, T. 41 N., R. 43 E., heretofore described, bears N. 89° 58' W., 38.44 chs. dist.

Land, gently rolling.
Soil, sandy clay loam.
Undergrowth, sagebrush and shadscale.

The point for the N. ¼ sec. cor. of sec. 3 is on the Eighth Standard Parallel North and at midpoint in departure on the N. bdy. of sec. 3.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T41N R43E

¼ S 3
T40N
1965