

SUBDIVISION OF T. 40 N., R. 43 E.

CHAINS
 51.60 Spur, slopes SSW. from NW.; asc. 40 ft. over a SW. slope.
 60.20 Point of spur, slopes S.; desc. 40 ft. over an ESE. slope.
 65.30 Ravine, drains SW.; asc. 90 ft. over a W. slope.
 72.10 Ridge, bears SSE. and NNW.; desc. 90 ft. over an E. slope.
 77.31 Intersect the W. bdy. of T. 40 N., R. 44 E.

Point for the closing cor. of secs. 24 and 25.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T40N
 R43E R44E
 CC $\frac{S\ 24}{S\ 25}$ | S 19
 1965

raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

from this corner

The cor. of secs. 19 and 30, T. 40 N., R. 44 E., heretofore described, bears S. $1^{\circ} 07' W.$, 6.22 chs. dist.

The W. $\frac{1}{4}$ sec. cor. of sec. 19, T. 40 N., R. 44 E., heretofore described, bears N. $1^{\circ} 07' E.$, 33.92 chs. dist.

Land, rolling and broken.
 Soil, sandy clay and rocky.
 Undergrowth, sagebrush and shadscale.

The point for the E. $\frac{1}{4}$ sec. cor. of sec. 25 is on the W. bdy. of T. 40 N., R. 44 E., and at midpoint in latitude on the E. bdy. of sec. 25.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T40N
 R43E R44E
 $\frac{1}{4}$ |
 S 25 |
 1965

raise a mound of stone, $3\frac{1}{2}$ ft. base, 3 ft. high, W. of cor.

from this corner

The W. $\frac{1}{4}$ sec. cor. of sec. 30, T. 40 N., R. 44 E., heretofore described, bears S. $0^{\circ} 23' W.$, 6.80 chs. dist.

The cor. of secs. 19 and 30, T. 40 N., R. 44 E., heretofore described, bears N. $0^{\circ} 23' E.$, 33.81 chs. dist.