

SUBDIVISION OF T. 40 N., R. 43 E.

CHAINS	
	<p>in the ground, with brass cap mkd.</p> <p style="text-align: center;">T40N R43E $\frac{1}{4}$ $\frac{S \ 14}{S \ 23}$ 1965</p> <p>raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor.</p> <p>Desc. 20 ft. over a NE. slope.</p>
42.10	Wash, 20 lks. wide, 5 ft. deep, drains NNW.; asc. 100 ft. over a steep SW. slope.
49.40	Begin ascent of 50 ft. over a gradual W. slope.
67.40	Ridge, bears N. and S.; desc. 90 ft. over an E. slope.
75.40	Wash, 10 lks. wide, 2 ft. deep, drains N.; asc. 60 ft. over a W. slope.
79.98	The cor. of secs. 13, 14, 23 and 24.
	<p>Land, rolling and broken. Soil, sandy clay and rocky. Undergrowth, sagebrush.</p>
	<p>EAST, bet. secs. 13 and 24.</p> <p>Over rolling land, through medium undergrowth; asc. 80 ft. over a W. slope.</p>
5.00	Slope changes; asc. 50 ft. along a N. slope.
14.30	Spur, slopes NNE.; desc. 100 ft. over an E. slope.
24.00	Wash, 10 lks. wide, 3 ft. deep, drains N.; asc. 150 ft. over a NW. slope.
40.00	Point for the ¼ sec. cor. of secs. 13 and 24.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T40N R43E $\frac{1}{4}$ $\frac{S \ 13}{S \ 24}$ 1965</p> <p>raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor.</p> <p>Asc. 310 ft. over a NW. slope.</p>
57.80	Spur, slopes NNE.; desc. 240 ft. over an E. slope.
72.30	Wash, 10 lks. wide, 2 ft. deep, drains N.; asc. 130 ft. over a W. slope.
78.73	Intersect the W. bdy. of T. 40 N., R. 44 E.