

## SUBDIVISION OF T. 40 N., R. 43 E.

CHAINS	
	Over rolling land, through medium undergrowth; desc. 70 ft. over a gradual N. slope.
27.70	Wash, 15 lks. wide, 3 ft. deep, drains NW.; asc. 50 ft. over a SW. slope.
35.50	Begin descent of 30 ft. over a NW. slope.
37.90	Ravine, drains WSW.; asc. 40 ft. over a SW. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T40N R43E  <math>\frac{1}{4}</math>  S 1   S 2  1965</p>
	<p>raise a mound of stone, 3 ft. base, <math>2\frac{1}{2}</math> ft. high, W. of cor.</p> <p>Asc. 90 ft. over a SW. slope.</p>
45.80	Top of ascent, bears ESE. and WNW.; desc. 70 ft. over a N. slope.
57.00	Ravine, drains NW.
63.40	Intersect the Eighth Standard Parallel North.
	Point for the closing cor. of secs. 1 and 2.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T41N R43E  S 35  S 2   S 1  CC  T40N  1965</p>
	<p>raise a mound of stone, <math>2\frac{1}{2}</math> ft. base, 2 ft. high, S. of cor.</p> <p>from this corner</p>
	<p>The standard <math>\frac{1}{4}</math> sec. cor. of sec. 35, T. 41 N., R. 43 E., heretofore described, bears N. <math>89^{\circ} 31'</math> E., 2.01 chs. dist.</p>
	<p>The standard cor. of secs. 34 and 35, T. 41 N., R. 43 E., heretofore described, bears S. <math>89^{\circ} 31'</math> W., 37.92 chs. dist.</p>
	<p>Land, rolling.  Soil, sandy clay loam.  Undergrowth, sagebrush.</p>
	<p>The point for the N. <math>\frac{1}{4}</math> sec. cor. of sec. 2 is on the Eighth Standard Parallel North and at midpoint in departure</p>