

DEPENDENT RESURVEY OF THE SECOND STANDARD PARALLEL NORTH
(SOUTH BOUNDARY - T. 11 N., R. 64 E.)

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

S	C
T11N	R64E
<u>S 31</u>	<u>S 32</u>

1964

raise a mound of stone, 4 ft. base, 3 ft. high, N. of cor.

Land, gently rolling.
Soil, sandy and gravelly, stony.
Timber, pinon and juniper.
Undergrowth, sagebrush.

N. 89° 53' W., along the S. bdy. of sec. 31.

Over rolling land, through scattering timber and medium heavy undergrowth; desc. 140 ft. over WSW. slope.

19.80 Ravine, drains WSW.

39.195 Point for the standard ¼ sec. cor. of sec. 31, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.

S	C
T11N	R64E
<u>¼</u>	<u>S 31</u>

1964

Continue measurement over rolling land, through scattering timber; desc. 160 ft. over W. slope.

74.70 Road, improved, bears N. and S.

77.60 Wash, 25 lks. wide, 7 ft. deep, drains SSE.

78.39 The standard corner of T. 11 N., Rs. 63 and 64 E., monumented with the remains of a squared wooden post, 4 ins. square, 18 ins. long, firmly set in the ground, alongside a stone, 14x12x9 ins., and in a mound of stone and marked and witnessed as described in the official record.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

S	C
T 11 N	
R63E	R64E
<u>S 36</u>	<u>S 31</u>

1964