

DEPENDENT RESURVEY OF THE WEST BOUNDARY  
T. 11 N., R. 64 E.

## CHAINS

- 39.71 Point for the  $\frac{1}{4}$  sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap mkd.
- T 11 N  
R63E R64E  
 $\frac{1}{4}$   
S 12 | S 7  
1964
- raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, W. of cor.
- Continue measurement over gently rolling land, through scattering undergrowth.
- 52.40 Wash, 5 lks. wide, 1 ft. deep, drains ESE.; asc. 20 ft. over SW. slope.
- 79.42 Point for the cor. of secs. 1, 6, 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap mkd.
- T 11 N  
R63E R64E  
S 1 | S 6  
S 12 | S 7  
1964
- from which
- A juniper, 8 ins. diam., bears S.  $81\frac{3}{4}^{\circ}$  W., 62 lks. dist., mkd. T11N R63E S12 BT.
- No other suitable bearing trees available.
- Land, gently rolling.  
Soil, sandy and gravelly clay loam.  
Timber, pinon and juniper.  
Vegetation, sagebrush.
- 
- N.  $0^{\circ} 44'$  W., bet. secs. 1 and 6.
- Over gently rolling land, through scattering timber and medium heavy undergrowth.
- 5.20 Trail road, bears NW. and SE.
- 5.40 Wash, 10 lks. wide, 1 ft. deep, drains E.; asc. 40 ft. over S. slope.