

DEPENDENT RESURVEY OF A PORTION OF THE FIRST STANDARD
PARALLEL SOUTH THROUGH RANGE 60 EAST

CHAINS

- 69.90 Small spur, slopes SW.; desc. 100 ft. over a broken W. slope.
- 75.90 Wash, 10 lks. wide, 2 ft. deep, drains SW.; asc. 20 ft. over a SE. slope.
- 78.57 The standard cor. of secs. 35 and 36, monumented with a limestone, 18x12x8 ins., firmly set in a small mound of stone, plainly mkd. 5 notches on W. edge, 1 notch on E. edge and SC on S. face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

SC
T4S R60E
S 35 | S 36
1964

bury the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of the iron post.

Land, broken.
Soil, clay, rocky.
Undergrowth, greasewood, creosote brush

DEPENDENT RESURVEY OF A PORTION OF THE N. BDY., T. 6 S.,
R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

Re-establishment of the survey executed by E. B.
Monroe, Deputy Surveyor, in 1870

From the corner of secs. 5, 6, 31 and 32 on the N. bdy. of T. 6 S., R. 61 E., monumented with a stone, 10x6x3 ins., firmly set in a mound of stone, dimly mkd. 5 notches on E. face and 1 notch on W. face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T5S R61E
S 31 | S 32
S 6 | S 5
T6S
1964

bury the original cornerstone alongside the iron post and raise a mound of stone, 2½ ft. base, 1 ft. high, W. of the iron post.

N. 89° 47' W., bet. secs. 6 and 31.

Over rolling land; desc. 130 ft. over W. slope.

- 24.70 Trail road, bears NE. and SW.
- 26.40 Wash, 15 lks. wide, 2 ft. deep, drains SW.; asc. 120 ft. over a SE. slope.