

DEPENDENT RESURVEY OF FIRST STANDARD PARALLEL SOUTH,
THROUGH RANGE 64 EAST

CHAINS	
	SC T4S R64E R65E <u>S 36 S 31</u>
	1965
	bury the original corner stone alongside the iron post and raise a mound of stone, 4 ft. base, 3 ft. high, N. of cor.
	S. 89° 11' W., along the S. bdy. of sec. 36.
	Over mountainous land; desc. 110 ft. over W. slope.
7.00	Ravine, drains SE.; asc. 180 ft. over E. slope.
19.00	Ridge, bears NE. and SW.; desc. 390 ft. over NW. slope.
31.65	The closing cor. of T. 5 S., Rs. 64 and 65 E., hereinafter described.
37.20	Spur, slopes NNW.; desc. 70 ft. over W. slope.
39.03	The standard $\frac{1}{4}$ sec. cor. of sec. 36, monumented with a granite stone, 12x8x6 ins., firmly set and mkd. $\frac{1}{4}$ on N. face.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground to bedrock and in a mound of stone to top, 4 ft. base, with brass cap mkd.
	SC T4S R64E <u>$\frac{1}{4}$ S 36</u>
	1965
	bury the original corner stone alongside the iron post.
	S. 89° 49' W., beginning new measurement.
	Desc. 80 ft. over W. slope.
2.30	Ravine, drains NNW.; asc. 120 ft. over NE. slope.
5.30	Spur, slopes N.; desc. 500 ft. over NW. slope.
32.56	The $\frac{1}{4}$ sec. cor. of sec. 1, T. 5 S., R. 64 E., hereinafter described.
40.88	The standard cor. of secs. 35 and 36, monumented with a granite stone, 12x10x8 ins., firmly set and mkd. 1 notch on E. face and 5 notches on W. face.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	SC T4S R64E <u>S 35 S 36</u>
	1965