

SURVEY OF THE E. BDY., T. 5 S., R. 64 E.

CHAINS	
	<p>raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Land, rolling and mountainous. Soil, shallow clay. Timber, juniper and pinon. Vegetation, greasewood.</p>
	<p>NORTH, along the E. bdy. of sec. 12.</p> <p>Over mountainous land; asc. 70 ft. over S. slope.</p>
11.60	Graded road, bears NW. and SE.; asc. 300 ft. over SW. slope.
33.40	Spur, slopes W.; desc. 200 ft. over NW. slope.
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of sec. 12.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground to bedrock and in a mound of stone to top, 4 ft. base, with brass cap mkd.</p> <div style="text-align: center;"> <p>T5S R64E R65E $\frac{1}{4}$ S 12</p> <p>1965</p> </div>
	<p>Desc. 120 ft. over N. slope.</p>
48.20	Wash, 30 lks. wide, 3 ft. deep, drains NW.; asc. 60 ft. over S. slope.
53.20	Spur, slopes SW.; desc. 30 ft. over a NW. slope.
56.40	Head of wash, drains SW.; asc. 110 ft. over a S. slope.
63.40	Ridge, bears W. and NE.; desc. 30 ft. over NW. slope.
72.30	Spur, slopes NW.; desc. 120 ft. over a N. slope.
79.20	Wash, 15 lks. wide, 2 ft. deep, drains NW.; asc. 30 ft. over a S. slope.
80.00	<p>Point for the cor. of secs. 1 and 12.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T5S R64E R65E S 1 S 12</p> <p>1965</p> </div> <p>raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Land, rolling and mountainous. Soil, shallow clay. Timber, juniper and pinon. Vegetation, greasewood.</p>
	<p>NORTH, along the E. bdy. of sec. 1.</p>