SUBDIVISION OF T. 5 S., R. 64 E.

_		5555171516N 01 1. 5 5., R. 04 1.
	CHAINS	
	11.50	Base of descent, bears NW. and SE.; desc. 110 ft. over rolling N. slope.
,	40.00	Point for the ½ sec. cor. of secs. 1 and 2.
		Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
		T5S R64E
		S 2 S 1
		1965
		raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	40.50	Wash, 50 1ks. wide, 3 ft. deep, drains W.
	46.70	Bladed road, bears E. and W.
	69.80	Intersect the First Standard Parallel South.
		Point for the closing corner of secs. 1 and 2.
		Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground and in a collar of stone, with brass cap mkd.
		T4S R64E S 35 S 2 S 1 CC T5S
		1965
		From this cor., the standard ½ sec. cor. of sec. 35, bears S. 89° 34' W., 8.47 chs. dist.
		Land, mountainous and rolling. Soil, shallow clay. Vegetation, greasewood and shadscale. Timber, juniper and pinon.
		The point for the N. ½ sec. cor. of sec. 1 on the First Standard Parallel South and at midpoint on the N. bdy. of sec. 1.
		Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
		T4S R64E
		表 S 1 T5S
		1965
		raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.
1		