

SUBDIVISION OF T. 5 S., R. 64 E.

CHAINS	
	<p>From this corner, the standard cor. of secs. 35 and 36, bears S. 89° 49' W., 8.32 chs. dist.</p>
	<p>From the cor. of secs. 2, 3, 34 and 35 on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set mkd. and witnessed as described in the field note record of the survey of T. 6 S., R. 64 E., executed concurrently under this same Group.</p> <p>N. 0° 01' W., bet. secs. 34 and 35.</p> <p>Over rolling land, through medium Joshua trees.</p>
3.10	Trail road, bears NE. and WSW.
18.60	Helene Wash, 30 lks. wide, 2 ft. deep, drains SSW.
21.20	Trail road, bears NE. and SW.
28.20	Trail road, bears NE. and SW.
32.90	Trail road, bears NE. and SW.
39.50	Wash, 30 lks. wide, 2 ft. deep, drains SW.
40.00	<p>Point for the ¼ sec. cor. of secs. 34 and 35.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T5S R64E</p> <p>¼</p> <p>S 34   S 35</p> <p>1965</p> </div> <p>raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
52.60	Wash, 15 lks. wide, 2 ft. deep, drains SW.
67.30	Wash, 10 lks. wide, 3 ft. deep, drains W.
80.00	<p>Point for the cor. of secs. 26, 27, 34 and 35.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock and in a mound of stone to top, 4 ft. base, with brass cap mkd.</p> <div style="text-align: center;"> <p>T5S R64E</p> <p>S 27   S 26</p> <p>S 34   S 35</p> <p>1965</p> </div> <p>Land, rolling.</p> <p>Soil, shallow clay and rocky.</p> <p>Vegetation, greasewood, Joshua trees and cacti.</p>
	<p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>N. 89° 58' W., bet. secs. 26 and 35.</p>