

## SUBDIVISION OF T. 5 S., R. 64 E.

CHAINS	
48.20	Wash, 20 lks. wide, 2 ft. deep, drains NW.; asc. 100 ft. over NE. slope.
53.70	Spur, slopes NW.; desc. 240 ft. over SW. slope.
68.30	Head of wash, drains NW.; asc. 120 ft. over NE. slope.
75.30	Spur, slopes NW.; desc. 130 ft. over W. slope.
79.90	The cor. of secs. 2, 3, 10 and 11.
	Land, mountainous. Soil, shallow clay and rocky. Vegetation, greasewood and cacti.
	N. 0° 01' W., bet. secs. 2 and 3.  Over mountainous land; desc. 80 ft. along W. slope.
7.30	Small wash, drains W.; enter rolling land.
23.00	Wash, 20 lks. wide, 2 ft. deep, drains WSW.
32.20	Water line, bears WSW. and ENE.
32.30	Fence, bears E. and W.
36.20	Bladed road, bears E. and W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T5S R64E
	S 3 $\frac{1}{2}$ S 2
	1965
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	from which:
	A concrete water trough, bears S. 46° 15' E., 9.90 chs. dist.
	NE. cor. of a wood corral, bears N. 89° 20' W., 14.85 chs. dist.
41.60	Fence, bears E. and W.
50.00	Bladed road, bears NE. and SW.
64.50	Wash, 30 lks. wide, 2 ft. deep, drains W.
69.79	Intersect the First Standard Parallel South.
	Point for the closing cor. of secs. 2 and 3.