## SUBDIVISION OF T. 5 S., R. 64 E.

CHAINS

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

1965

raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this cor., the standard  $\frac{1}{4}$  sec. cor. of sec. 34, bears S. 89° 49' W., 9.03 chs. dist.

Land, mountainous and rolling. Soil, shallow clay and rocky. Vegetation, greasewood and cacti.

The point for the N.  $\frac{1}{4}$  sec. cor. of sec. 2 on the First Standard Parallel South and at midpoint on the N. bdy. of sec. 2.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 8 ins. in the ground to bedrock and in a mound of stone to top, 5 ft. base, with brass cap mkd.

T4S R64E

1965

From this corner, the standard cor. of secs. 34 and 35, bears S.  $89^{\circ}$   $48^{\circ}$  W., 8.82 chs. dist.

From the cor. of secs. 3, 4, 33 and 34 on the S. bdy. of the Tp., monumented with an iron post,  $2\frac{1}{2}$  ins. diam., set mkd. and witnessed as described in the field note record of the survey of T. 6 S., R. 64 E., executed concurrently under this same Group.

N. 0° 02' W., bet. secs. 33 and 34.

Over rolling land, through scattered Joshua trees.

22.70 Trail road, bears NW. and SE.

30.10

Wash, 15 1ks. wide, 2 ft. deep, drains SW.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 33 and 34.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

1965

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.