

SUBDIVISION OF T. 5 S., R. 64 E.

CHAINS	
67.50	Bladed road, bears NNE. and SSW.
80.06	The cor. of secs. 3, 4, 9 and 10. Land, broken and rolling. Soil, sandy loam. Vegetation, greasewood and Joshua trees.
	N. 0° 02' W., bet. secs. 3 and 4. Over rolling land, through scattered Joshua trees; asc. gentle SW. slope.
21.70	Bladed road, bears E. and W.
36.90	Water line, bears E. and W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. T5S R64E $\frac{1}{4}$ S 4 S 3 1965 raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
67.40	Wash, 15 lks. wide, 2 ft. deep, drains SW.
69.63	Intersect the First Standard Parallel South. Point for the closing cor. of secs. 3 and 4. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. T4S R64E S 33 S 4 S 3 CC T5S 1965 raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor. From this cor., the standard $\frac{1}{4}$ sec. cor. of sec. 33, bears S. 89° 58' W., 9.52 chs. dist. Land, rolling. Soil, sandy loam. Vegetation, greasewood and Joshua trees.
	The point for the N. $\frac{1}{4}$ sec. cor. of sec. 3 on the First Standard Parallel South and at midpoint on the N. bdy. of sec. 3.