

SUBDIVISION OF T. 5 S., R. 64 E.

CHAINS	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p>T4S R64E</p> <div><div>½ S 3</div><div>T5S</div></div> <p>1965</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.</p> <p>From this corner, the standard cor. of secs. 33 and 34, bears S. 89° 58' W., 9.355 chs. dist.</p>
	<p>From the cor. of secs. 4, 5, 32 and 33 on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field note record of the survey of T. 6 S., R. 64 E., executed concurrently under this same group.</p> <p>N. 0° 03' W., bet. secs. 32 and 33.</p> <p>Over level land, through medium dense Joshua trees.</p> <p>0.80 Wash, 10 lks. wide, 2 ft. deep, drains WSW.</p> <p>6.30 Graded road, bears NW. and SE.</p> <p>19.20 Wash, 30 lks. wide, 3 ft. deep, drains WSW.</p> <p>39.20 Wash, 10 lks. wide, 2 ft. deep, drains W.</p> <p>40.00 Point for the ¼ sec. cor. of secs. 32 and 33.</p> <p>Set an iron post, 28 ins. long, 2½ ins.diam., 24 ins. in the ground, with brass cap mkd.</p> <p>T5S R64E</p> <div><div>½</div><div>S 32 S 33</div></div> <p>1965</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>44.20 Wash, 20 lks. wide, 2 ft. deep, drains W.</p> <p>80.00 Point for the cor. of secs. 28, 29, 32 and 33.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div><div>T5S R64E</div><div><div>S 29 S 28</div><div>S 32 S 33</div></div></div> <p>1965</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>