SUBDIVISION OF T. 5 S., R. 64 E

 4	SUBDIVISION OF T. 5 S., R. 64 E.
CHAINS	From the cor. of secs. 3, 4, 9 and 10.
	N. 89° 58' W., bet. secs. 4 and 9.
	Over rolling land, through scattered Joshua trees; desc. gentle W. slope.
8.00	Wash, 20 1ks. wide, 2 ft. deep, drains WSW.
32.30	Graded road, bears NNW. and SSE.
40.00	Point for the ½ sec. cor. of secs. 4 and 9.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T5S R64E 12 S 4 S 9
	1965
	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
48.10	Power line, bears N. 21½° E. and S. 21½° W.
49.10	Graded road, parallel to power line.
56.50	Bladed road, bears NW. and SE.
80.00	The cor. of secs. 4, 5, 8 and 9.
	Land, rolling. Soil, sandy loam. Vegetation, greasewood and Joshua trees.
	N. 0° 03' W., bet. secs. 4 and 5.
	Over gently rolling land, through scattered Joshua trees.
15.20	Trail road, bears E. and W.
18.80	Bladed road, bears NW. and SE.
40.00	Point for the ½ sec. cor. of secs. 4 and 5.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T5S R64E
	S 5 S 4
·	1965
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
69.60	Intersect the First Standard Parallel South.
	Point for the closing cor. of secs. 4 and 5.