SOUTH BOUNDARY OF T. 6 S., R. 64 E.

		SOUTH BOUNDARY OF T. 6 S., R. 64 E.	
	CHAINS 80.00	Point for the cor. of secs. 1, 2, 35 and 36.	
		Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.	
		T6S R64E S 35 S 36 S 2 S 1 T7S	
		1964	
		raise a mound of stone, 3 ft. base, 2 ft. high, W. of	
		cor.	
		Land, rolling and broken. Soil, clay and rocky. Vegetation, greasewood and shadscale.	
		EAST, bet. secs. 1 and 36.	
	•	Over rolling land; asc. gentle W. slope.	
	6.80	Trail road in bottom of wash draining NW., bears NW. and SE.; asc. 110 ft.	
	31.30	Wash, 20 1ks. wide, 3 ft. deep, drains WSW. from E.	
	33.00	Leave wash from ESE.; asc. 40 ft.	
	38.80	Same wash, drains WSW.	
	40.00	Point for the 2 sec. cor. of secs. 1 and 36.	
	, .	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.	
		T6S R64E 2 S 36 S 1 T7S	
		1964	
		raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.	
	42.10	Same wash, drains WNW.; asc. 30 ft.	
	44. 60	Same wash, drains WSW.; asc. 20 ft.	
	47.90	Same wash, drains WNW.; asc. 70 ft.	
	57.90	Same wash, drains WSW.; asc. 310 ft. over NW. slope.	
	80.00	Point for the cor. of Tps. 6 and 7 S., R. 64 E. at cal- culated distance as shown on approved Protraction Diagrams Nos. 200 and 201.	
		Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock and in a mound of stone, 5 ft. base to top, with brass cap mkd.	
		T6S R64E R65E S 36 S 1 T7S	
لِ		1964	