

EAST BOUNDARY OF T. 6 S., R. 64 E.

CHAINS	<p>Cor. No. 2 of M.S. 1808, Dornerburg, monumented with a wooden post, 4 ins. square, set, mkd. and witnessed as described in the official record, bears N. 78° 25' W., 28.96 chs. dist.</p> <p>Asc. 110 ft. over SSW. slope.</p> <p>57.30 Head of wash, drains SE.; asc. 270 ft. over SE. slope.</p> <p>74.20 Wash, 10 lks. wide, 2 ft. deep, drains SE.; asc. 110 ft. over SE. slope.</p> <p>80.00 Point for the cor. of secs. 1 and 12.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone to top, 5 ft. base, with brass cap mkd.</p> <div><div>T6S</div><div>R64E R65E</div><div>S 1 </div><div>S 12 </div></div> <p>1965</p> <p>from which</p> <p>U.S.M.M. No. 2 of the Ferguson Mining Dist. (Office No. 120), monumented with a stone, 40x30x30 ins., mkd. U.S.L.M. 2 and with an X, set in a mound of stone, bears N. 63° 09' W., 23.73 chs. dist.</p> <p>Land, rolling and mountainous. Soil, sandy loam, clay and rocky. Timber, scattered juniper and pinon. Undergrowth, greasewood and shadscale.</p>	
	<p>NORTH, along the east bdy. of sec. 1.</p> <p>Over mountainous land, through scattered timber; asc. 760 ft. over SE. slope.</p> <p>40.00 Point for the ¼ sec. cor. of sec. 1.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., on an X on solid rock and in a mound of stone to top, 5 ft. base, with brass cap mkd.</p> <div><div>T6S</div><div>R64E R65E</div><div>¼ </div><div>S 1 </div></div> <p>1965</p> <p>Asc. 70 ft. over SE. slope.</p> <p>43.10 Ridge, bears NE. and SW.; desc. 400 ft. over NW. slope.</p> <p>59.10 Ravine, drains W.; asc. 330 ft. over SW. slope.</p>	