

TOWNSHIP 17 NORTH, RANGE 32 EAST

CHAINS

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 17 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

Re-establishment of the Survey Executed by E. B.
Monroe, Deputy Surveyor, in 1868.

Beginning at the cor. of secs. 25, 30, 31 and 36, T. 17 N.,
Rs. 31 and 32 E., monumented with an iron post, set, mkd.
and witnessed as described in the field notes of the
resurvey of the W. bdy. of Sec. 31, T. 17 N., R. 32 E. in
1915.

N. 1° 14' W., along the E. bdy. of sec. 25.

Over rolling land, through medium undergrowth; asc. 90 ft.
over a S. slope.

39.99 The $\frac{1}{4}$ sec. cor. of sec. 30, T. 17 N., R. 32 E., hereinafter
described.

40.49 Point for the $\frac{1}{4}$ sec. cor. of sec. 25, at proportionate dis-
tance; there is no remaining evidence of the original cor.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in
the ground, with brass cap mkd. for the $\frac{1}{4}$ sec. cor. of
sec. 25 only.

T17N
R31E R32E
 $\frac{1}{4}$ |
S 25 |
1964

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Asc. 20 ft. over S. slope.

53.40 Unimproved road, bears E. and W.; asc. 30 ft. over a S.
slope.

66.20 Wash, 10 lks. wide, 2 ft. deep, drains SE.; asc. 80 ft.
over a S. slope.

79.97 The closing corner of secs. 19, and 30, T. 17 N., R. 32 E.
hereinafter described.

80.98 The cor. of secs. 19, 24, 25 and 30, monumented with a
lava stone, 12x10x8 ins., firmly set in a mound of stone
and plainly mkd. with 2 notches on the S. face and 4 not-
ches on the N. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in
the ground and in a collar of stone, with brass cap mkd.
for the cor. of secs. 24 and 25, T. 17 N., R. 31 E., only.

T17N
R31E R32E
S 24 | S 19
S 25 |
1964

bury the original cornerstone alongside the iron post.