

## SUBDIVISION OF T. 17 N., R. 32 E.

CHAINS

T17N R32E  
 $\frac{1}{4}$  S 19  
 S 30  
 1964

48.30 Wash, 10 lks. wide, 3 ft. deep, drains S.

56.00 Narrow wash, 5 ft. deep, drains S.

63.30 Wash, 20 lks. wide, 3 ft. deep, drains S.

70.30 Wash, 10 lks. wide, 3 ft. deep, drains SW.

81.86 Intersect the E. bdy. of T. 17 N., R. 31 E.

Point for the closing corner of secs. 19 and 30.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 8 ins. in the ground and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T17N  
 R32E  
 R31E S 19<sup>CC</sup>  
 S 25 S 30  
 1964

from which

The cor. of secs. 24 and 25, T. 17 N., R. 31 E., bears N.  $1^{\circ} 14'$  W., 1.01 chs. distance, heretofore described.

Land, rolling.

Soil, sandy and stony.

Undergrowth, shadscale and sparse bunchgrass.

The point for the W  $\frac{1}{4}$  sec. cor. of sec. 30 is at mid-point and on the W. bdy. of the Tp.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground and in a collar of stone with brass cap mkd.

T17N  
 R31E R32E  
 $\frac{1}{4}$   
 S 30  
 1964

from which

The  $\frac{1}{4}$  sec. cor. of sec. 25, T. 17 N., R. 31 E., bears N.  $1^{\circ} 14'$  W., 0.50 chs. distance, heretofore described.

From the cor. of secs. 19, 20, 29 and 30.

N.  $0^{\circ} 03'$  W., bet. secs. 19 and 20.

Over rolling land, through medium undergrowth; asc. 170 ft. over a S. slope.