	SURVEY OF A PORTION OF THE SUBDIVISION OF T. 20 N., R. 34 E.
CHAINS	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T20N R34E 1 S 1 2 S 12
	1965
	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
79.98	The cor. of secs. 1, 2, 11, and 12.
	Land, nearly level. Soil, sandy loam. Undergrowth, sagebrush, and shadscale.
	N. 0° 01' W., between secs. 1 and 2.
	Over nearly level land, draining N., through medium undergrowth.
13.00	Wash, 10 1ks. wide, 2 ft. deep, drains NE.
40.00	Point for the 1 sec. cor. of secs. 1 and 2.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T20N R34E
	S 2 S 1
	1965
	raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.
62.00	Emergency landing strip (earth), 50 ft. wide, bears N. 35½° E. for approximately 25.00 chs. distance and S. 35½° W. for approximately 25.00 chs.
83.10	Bladed dirt road, bears E. and W.
83.40	Fence, bears E. and W.
83.91	Intersect the Fourth Standard Parallel North.
	Point for the closing cor. of secs. 1 and 2.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T21N R34E S 36
	S 2 S 1 CC T20N R34E
	1965