

## SURVEY OF A PORTION OF THE SUBDIVISION OF T. 20 N., R. 34 E.

## CHAINS

Over nearly level land, draining NE., through medium undergrowth.

17.20 Wash, 10 lks. wide, 2 ft. deep, drains NE.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 2 and 3.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T20N R34E

$\frac{1}{4}$   
S 3 | S 2

1965

raise a mound of stone,  $2\frac{1}{2}$  ft. base, 2 ft. high, W. of cor.

84.00 Intersect the Fourth Standard Parallel North.

Point for the closing cor. of secs. 2 and 3.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T21N R34E

S 35  
S 3 | S 2

CC

T20N R34E

1965

raise a mound of stone,  $2\frac{1}{2}$  ft. base, 2 ft. high, S. of cor.

From this cor., the standard cor. of secs. 34 and 35, T. 21 N., R. 34 E., bears N.  $89^{\circ} 59'$  W., 9.44 chs. dist.

From this same cor., the standard  $\frac{1}{4}$  sec. cor. of sec. 35, T. 21 N., R. 34 E., bears S.  $89^{\circ} 59'$  E., 30.56 chs. dist.

Land, nearly level.

Soil, sandy clay.

Undergrowth, sagebrush.

The point for the N.  $\frac{1}{4}$  sec. cor. of sec. 2 is on the Fourth Standard Parallel North and at midpoint on the N. bdy. of sec. 2, falls in the center of a bladed dirt road, bearing E. and W.

Set a copper-coated steel stake, 18 ins. long,  $\frac{1}{2}$  in. diam., 18 ins. below the surface of the road, with brass cap,  $1\frac{1}{2}$  ins. diam., mkd.

T21N R34E

$\frac{1}{4}$  S 2  
T20N R34E

1965