

SURVEY OF A PORTION OF THE SUBDIVISION OF T. 20 N., R. 34 E.

CHAINS	raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor. Land, gently rolling. Soil, sandy and rocky. Undergrowth, sagebrush.
	From the cor. of secs. 3, 4, 9, and 10. S. 89° 58' W., between secs. 4 and 9. Over gently rolling land, draining NE., through medium undergrowth.
7.20	Improved gravel road, bears N. and S.; asc. 80 ft. over gradual E. slope.
40.00	Point for the ¼ sec. cor. of secs. 4 and 9. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. <div>T20N R34E S 4 ¼ S 9 1965</div>
	raise a mound of stone, 2½ ft. base, 2 ft. high, N. of cor. Asc. 130 ft. over E. slope.
80.00	The cor. of secs. 4, 5, 8, and 9, Land, gently rolling. Soil, sandy and rocky. Undergrowth, sagebrush.
	N. 0° 03' W., bet. secs. 4 and 5. Desc. 60 ft. over gentle NE. slope, with numerous small washes draining E., through medium undergrowth.
40.00	Point for the ¼ sec. cor. of secs. 4 and 5. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. <div>T20N R34E S 5 ¼ S 4 1965</div>
	raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.
51.80	Bladed dirt road, bears E. and W.
84.15	Intersect the Fourth Standard Parallel North. Point for the closing cor. of secs. 4 and 5.