

DEPENDENT RESURVEY, FIFTH STANDARD PARALLEL NORTH,
THROUGH RANGE 61 EAST

CHAINS	
	<p>bury the original corner post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>Land, nearly level. Soil, sandy clay loam. Undergrowth, sagebrush.</p>
<p>24.40</p> <p>40.23</p>	<p>S. 89° 51' W., along the S. bdy. of sec. 32.</p> <p>Over gentle rolling land, through medium undergrowth.</p> <p>Bladed road, bears SE. and NW.</p> <p>Point for the standard $\frac{1}{4}$ sec. cor. of sec. 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">SC T26N R61E <u>¼ S 32</u></p> <p style="text-align: center;">1965</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>Asc. 50 ft. over a gentle E. slope.</p>
<p>80.46</p>	<p>The standard cor. of secs. 31 and 32, monumented with a squared wooden post, 12 ins. long, 2 ins. square, plainly mkd. and loosely set in a mound of earth.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground with brass cap mkd.</p>
	<p style="text-align: center;">SC T26N R61E <u>S 31 S 32</u></p> <p style="text-align: center;">1965</p> <p>bury the original wooden post alongside the iron post and raise a mound of stone, 2½ ft. base, 2 ft. high, N. of cor.</p> <p>Land, gentle rolling. Soil, sandy clay loam. Undergrowth, sagebrush.</p> <p>S. 89° 15' W., along the S. bdy. of sec. 31.</p> <p>Over gentle rolling land, through medium undergrowth.</p>