

DEPENDENT RESURVEY, S. BDY., T. 10 N., R. 57 E.

CHAINS	
	N. 89°49' W., beginning new measurement.
	Over nearly level land, through scattering undergrowth, along S. edge of road bearing E. and W.
20.20	Well casing, bears SOUTH, 0.07 chs. dist.
31.40	Corner post of fence, bears NORTH, 0.02 chs. dist., fence bears S. and W.
40.25	The cor. of secs. 5, 6, 31 and 32, monumented with a squared wooden post, 30 ins. long, 2 ins. square, firmly set and marked as described in the official record. This corner sets near the corner post at the end of a fence line that bears E.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> T10N R57E S 31 S 32 S 6 S 5 T 9 N </div>
	1965
	reset the wooden post alongside the iron post and raise a mound of stone, 3½ ft. base, 2 ft. high, W. of cor.
	Land, level.
	Soil, sandy clay.
	Undergrowth, sagebrush and greasewood.
	N. 89°48' W., bet. secs. 6 and 31.
	Over nearly level land, through scattering undergrowth, along S. edge of road bearing E. and W.
1.30	Intermittent stream, 5 lks. wide, 1 ft. deep, course S.
7.50	Intermittent stream, 5 lks. wide, 1 ft. deep, course S.
11.50	Well casing, bears SOUTH 0.09 chs. dist.
39.98	The ¼ sec. cor. of secs. 6 and 31, monumented with a squared wooden post, 30 ins. long, 2 ins. square, loosely set in a mound of earth and marked as described in the official record.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> T10N R57E S 31 ¼ S 6 T 9 N </div>
	1965