

DEPENDENT RESURVEY, T. 10 N., R. 57 E.

CHAINS	
	raise a mound of stone $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.
41.50	Wash, 10 lks. wide, 1 ft. deep, drains SW.
80.34	Intersect the Second Standard Parallel North.
	Point for the closing cor. of secs. 2 and 3, T. 10 N., R. 57 E.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T11N R57E <u>S 34</u> S 3 S 2 T10N R57E C C</p>
	1965
	raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.
	From this corner, the angle point on the S. bdy. sec. 34, T. 11 N., R. 57 E., bears S. $89^{\circ} 44'$ E., 4.78 chs. dist., monumented with a $2\frac{1}{2}$ in. diam., iron post, set, marked and witnessed as described in the concurrent resurvey of the Second Stan. Par. N., through R. 57 E.
	From the same corner, the standard $\frac{1}{4}$ sec. cor. of sec. 34, T. 11 N., R. 57 E., bears N. $89^{\circ} 44'$ W., 33.23 chs. dist., monumented with a $2\frac{1}{2}$ in. diam., iron post, set, marked and witnessed as described in the concurrent resurvey of the Second Stan. Par. N., through R. 57 E.
80.47	The closing cor. of secs. 2 and 3, monumented with a wooden post, 40 ins. long, 4 ins. square, plainly marked and firmly set. This cor. will no longer function as a closing cor., but will now serve as an amended monument.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	AM
	1965
	reset the wooden post alongside the iron post.
	Land, level.
	Soil, sandy clay.
	Undergrowth, sagebrush and greasewood.
	Point for the N. $\frac{1}{4}$ sec. cor. of sec. 2, is on the Second Standard Parallel North and at midpoint on the N. bdy. of sec. 2.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.