

DEPENDENT RESURVEY, T. 10 N., R. 57 E.

CHAINS

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

AM

1965

reset the wooden post alongside the iron post.

41.25

Intersect the Second Standard Parallel North.

Point for the closing cor. of secs. 4 and 5, T. 10 N., R. 57 E.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T11N R57E

S 32

S 5 | S 4

T10N R57E

C C

1965

raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this corner, the angle point on the S. bdy. sec. 32, T. 11 N., R. 57 E., bears N. $89^{\circ} 34'$ E., 4.17 chs. dist., monumented with a $2\frac{1}{2}$ in diam. iron post, set, marked and witnessed as described in the concurrent resurvey of the Second Stan. Par. N., through R. 57 E.

From the same corner, the standard $\frac{1}{4}$ sec. cor. of sec. 32, T. 11 N., R. 57 E., bears S. $89^{\circ} 34'$ W., 31.98 chs. dist., monumented with a $2\frac{1}{2}$ in. diam. iron post, set, marked and witnessed as described in the concurrent resurvey of the Second Stan. Par. N., through R. 57 E.

Land, level.

Soil, sandy clay

Undergrowth, sagebrush and greasewood.

Point for the N. $\frac{1}{4}$ sec. cor. of sec. 4, is on the Second Standard Parallel North and at midpoint on the N. bdy. of sec. 4.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T11N R57E

$\frac{1}{4}$ S 4

T10N R57E

1965

raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.