

DEPENDENT RESURVEY, T. 10 N., R. 57 E.

CHAINS	
35.23	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp.</p> <p>Land, level. Soil, sandy clay. Undergrowth, sagebrush and greasewood.</p>
	<p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0° 39' E., bet. secs. 5 and 6.</p> <p>Over nearly level land, through scattering undergrowth.</p>
40.10	<p>The $\frac{1}{4}$ sec. cor. of secs. 5 and 6, monumented with a squared wooden post, 20 ins. long, 2 ins. square, loosely set in a mound of earth and marked as described in the official record.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N R57E $\frac{1}{4}$ S 6 S 5</p> <p style="text-align: center;">1965</p> <p>reset the wooden post alongside the iron post and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.</p>
	<p style="text-align: center;">_____</p> <p>N. 0° 14' W., beginning new measurement.</p> <p>Over nearly level land, through scattering undergrowth.</p>
41.37	<p>The closing cor. of secs. 5 and 6, monumented with a wooden post, 30 ins. long, 4 ins. square, plainly marked and firmly set. This cor. will no longer function as a closing cor., but will now serve as an amended monument.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">AM</p> <p style="text-align: center;">1965</p> <p>reset the wooden post alongside the iron post.</p>
41.67	<p>Intersect the Second Standard Parallel North.</p> <p>Point for the closing cor. of secs. 5 and 6, T. 10 N., R. 57 E.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>