

SECOND STANDARD PARALLEL NORTH, R. 57 E.

CHAINS	
35.56	<p>Point for the standard cor. of secs. 31 and 32, at 80.00 chs. in departure from the SE. cor. of sec. 32.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T11N R57E <u>S 31 S 32</u></p> <p style="text-align: center;">1965</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>Land, gently rolling. Soil, sandy clay. Undergrowth, sagebrush and greasewood.</p>
	<p>N. 89° 41' W., along the S. bdy. of sec. 31.</p> <p>Over gently rolling land, through scattering undergrowth.</p>
8.30	<p>The closing cor. of secs. 5 and 6, T. 10 N., R. 57 E., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of T. 10 N., R. 57 E., executed concurrently under this same group.</p>
40.00	<p>Point for the standard ¼ sec. cor. of sec. 31.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T11N R57E <u>¼ S 31</u></p> <p style="text-align: center;">1965</p> <p>raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor.</p>
48.74	<p>The ¼ sec. cor. of sec. 6, T. 10 N., R. 57 E., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of T. 10 N., R. 57 E., executed concurrently under this same group.</p>
84.47	<p>The standard cor. of T. 11 N., Rs. 56 and 57 E., monumented with a squared wooden post, firmly set and marked as described in the official record.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T11N R56E R57E <u>S 36 S 31</u></p> <p style="text-align: center;">1965</p>