

SURVEY OF T. 11 N., R. 57 E.

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} \text{T11N R57E} \\ \text{S 29} \\ \hline \frac{1}{4} \text{ S 32} \end{array}$
	1965
	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
43.20	Bull Creek, dry, 10 lks. wide, 2 ft. deep, drains SSE.
46.70	Wash, 10 lks. wide, 2 ft. deep, drains SSE.
79.96	The cor. of secs. 29, 30, 31 and 32.
	Land, level. Soil, sandy clay. Undergrowth, sagebrush.
	N. 89° 41' W., bet. secs. 30 and 31.
	Over nearly level land, through scattering undergrowth.
15.70	Duckwater Creek, dry, 40 lks. wide, 4 ft. deep, drains S.
40.00	Point for the ¼ sec. cor. of secs. 30 and 31.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} \text{T11N R57E} \\ \text{S 30} \\ \hline \frac{1}{4} \text{ S 31} \end{array}$
	1965
	deposit broken glass 6 ins. below surface alongside iron post.
	80
80.00	Point for the 1/16 sec. cor. of secs. 30 and 31.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} \text{T11N R57E} \\ \text{S 30} \\ \hline \frac{1}{16} \text{ S 31} \end{array} 80$
	1965
	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
85.65	Intersect the E. bdy. of sec. 36, T. 11 N., R. 56 E.
	Point for the closing cor. of secs. 30 and 31, T. 11 N., R. 57 E.