

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 12 N., R. 57 E.

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T12N R57E} \\ \text{S } 4 \\ \hline \frac{1}{4} \text{ S } 9 \end{array}$$

1965

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Desc. 40 ft. over gentle W. slope.

55.00 Wash, 30 lks. wide, 2 ft. deep, drains SW.; desc. 20 ft. over gentle W. slope.

62.70 Trail road, bears ENE. and WSW.; desc. 30 ft. over gentle W. slope.

80.02 The cor. of secs. 4, 5, 8 and 9.

Land, gently rolling.
Soil, sandy clay.
Undergrowth, sagebrush.

N. $0^{\circ} 03'$ W., bet. secs. 4 and 5.

Over gently rolling land, through scattered undergrowth.

5.50 Wash, 10 lks. wide, 1 ft. deep, drains WSW.; asc. 20 ft. over gentle SW. slope.

23.10 Bladed road, bears NE. and SW.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T12N R57E} \\ \frac{1}{2} \\ \text{S } 5 \text{ S } 4 \end{array}$$

1965

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Asc. 30 ft. over gentle SW. slope.

81.11 Intersect the S. bdy. of secs. 32, T. 13 N., R. 57 E.

Point for the closing cor. of secs. 4 and 5.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T13N R57E} \\ \text{S } 32 \\ \hline \text{S } 5 \text{ S } 4 \\ \text{T12N R57E} \\ \text{C C} \end{array}$$

1965