

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 12 N., R. 57 E.

CHAINS	
	WEST, bet. secs. 30 and 31.
	Over nearly level land, through scattered undergrowth.
18.20	Bull Creek, 10 lks. wide, 3 ft. deep, drains SSW.
27.30	Wash, 20 lks. wide, 3 ft. deep, drains SSW.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T12N R57E $\frac{1}{4}$ $\frac{S 30}{S 31}$
	1965
	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
83.22	Intersect the E. bdy. of sec. 36, T. 12 N., R. 56 E.
	Point for the closing corner of secs. 30 and 31.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T12N R56E R57E S 36 $\frac{S 30 C}{S 31 C}$
	1965
	raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.
	from this corner
	The cor. of secs. 25 and 36, T. 12 N., R. 56 E., heretofore described, bears N. $1^{\circ} 53' W.$, 11.95 chs. dist.
	The $\frac{1}{4}$ sec. cor. of sec. 36, T. 12 N., R. 56 E., heretofore described, bears S. $1^{\circ} 53' E.$, 28.41 chs. dist.
	Land, level.
	Soil, sandy clay.
	Undergrowth, sagebrush and greasewood.
	The point for the W. $\frac{1}{4}$ sec. cor. of sec. 31 is on the E. bdy. of T. 12 N., R. 56 E., and at midpoint on the W. bdy. of sec. 31.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T12N R56E R57E $\frac{1}{2}$ S 31
	1965