

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 12 N., R. 57 E.

CHAINS

80.10 Wash, 10 lks. wide, 2 ft. deep, drains S.

83.39 Intersect the E. bdy. of sec. 25, T. 12 N., R. 56 E.

Point for the closing cor. of secs. 19 and 30.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T12N
R56E R57E
S 25 | S 19 C
 | S 30 C

1965

raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.

from this corner

The cor. of secs. 24 and 25, T. 12 N., R. 56 E., heretofore described, bears N. $0^{\circ} 10'$ E., 11.86 chs. dist.

The $\frac{1}{4}$ sec. cor. of sec. 25, T. 12 N., R. 56 E., heretofore described, bears S. $0^{\circ} 10'$ W., 28.59 chs. dist.

Land, level.

Soil, sandy clay.

Undergrowth, sagebrush.

The point for the W. $\frac{1}{4}$ sec. cor. of sec. 30 is on the E. bdy. of T. 12 N., R. 56 E. and at midpoint on the W. bdy. of sec. 30.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T12N
R56E R57E
 $\frac{1}{4}$
| S 30

1965

raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.

from this corner

The $\frac{1}{4}$ sec. cor. of sec. 25, T. 12 N., R. 56 E., heretofore described, bears N. $0^{\circ} 18'$ E., 11.45 chs. dist.

The cor. of secs. 25 and 36, T. 12 N., R. 56 E., heretofore described, bears S. $0^{\circ} 18'$ W., 28.10 chs. dist.

From the cor. of secs. 19, 20, 29 and 30.

N. $0^{\circ} 03'$ W., bet. secs. 19 and 20.