

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 12 N., R. 57 E.

CHAINS

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Desc. 70 ft. over WSW. slope to cor.

48.60 Wash, 20 lks. wide, 3 ft. deep, drains SW.

56.50 Bladed road, bears WNW. and ESE

68.80 Wash, 10 lks. wide, 1 ft. deep, drains SW.

80.00 The cor. of secs. 17, 18, 19 and 20.

Land, gently rolling.

Soil, sandy clay.

Undergrowth, sagebrush.

WEST, bet. secs. 18 and 19.

Over nearly level land, through scattered undergrowth.

13.60 Trail road, bears NNE. and SSW.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T12N R57E} \\ \text{S 18} \\ \hline \frac{1}{4} \text{ S 19} \end{array}$$

1966

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

42.30 Bull Creek, 20 lks. wide, 3 ft. deep, drains S.

82.30 Wash, 20 lks. wide, 2 ft. deep, drains S.

83.59 Intersect the E. bdy. of sec. 24, T. 12 N., R. 56 E.

Point for the closing cor. of secs. 18 and 19.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T12N} \\ \text{R56E R57E} \\ \text{S 24} \left| \begin{array}{l} \text{S 18 C} \\ \text{S 19 C} \end{array} \right. \end{array}$$

1966

raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.

from this corner

The cor. of secs. 13 and 24, T. 12 N., R. 56 E., heretofore described, bears N. $0^{\circ} 22' W.$, 11.85 chs. dist.

The $\frac{1}{4}$ sec. cor. of sec. 24, T. 12 N., R. 56 E., heretofore described, bears S. $0^{\circ} 22' E.$, 28.09 chs. dist.