

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 12 N., R. 57 E.

CHAINS

52.70 Bull Creek, 20 lks. wide, 3 ft. deep, drains SSE.

56.00 Trail road, bears NW. and SE.

58.10 Wash, 10 lks. wide, 3 ft. deep, drains S.

75.00 Wash, 10 lks. wide, 2 ft. deep, drains S.

84.14 Intersect the E. bdy. of sec. 13, T. 12 N., R. 56 E.

Point for the closing cor. of secs. 7 and 18.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T12N
R56E R57E
S 13 | S 7 C
 | S 18 C

1966

raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.

from this corner

The cor. of secs. 12 and 13, T. 12 N., R. 56 E., heretofore described, bears N. 0° 35' W., 11.49 chs. dist.

The ¼ sec. cor. of sec. 13, T. 12 N., R. 56 E., heretofore described, bears S. 0° 35' E., 28.23 chs. dist.

Land, level.
Soil, sandy clay.
Undergrowth, sagebrush.

The point for the W. ¼ sec. cor. of sec. 18 is on the E. bdy. of T. 12 N., R. 56 E. and at midpoint on the W. bdy. of sec. 18.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T12N
R56E R57E
 | ¼
 | S 18

1966

raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.

from this corner

The ¼ sec. cor. of sec. 13, T. 12 N., R. 56 E., heretofore described, bears N. 0° 22' W., 11.78 chs. dist.

The cor. of secs. 13 and 24, T. 12 N., R. 56 E., heretofore described, bears S. 0° 22' E., 28.16 chs. dist.