

008

DEPENDENT RESURVEY OF THE SEVENTH STANDARD PARALLEL NORTH, RANGE 36 EAST

CHAINS

- raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor.
- 45.00 Dim trail road, bears N. and S.
- 45.425 The N. ¼ sec. cor. of sec. 5, hereinafter described. Over low rolling brush covered sand dunes.
- 80.52 Point for the standard cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
- SC
T36N R36E
S 31 | S 32
- 1965
- raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor.
- Land, gently rolling.
Soil, sandy clay.
Undergrowth, sagebrush.
-
- S. 89° 54' W., along the S. bdy. of sec. 31.
- Over low rolling brush covered sand dunes.
- 5.14 The closing cor. of secs. 5 and 6, hereinafter described.
- 40.26 Point for the standard ¼ sec. cor. of sec. 31, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
- SC
T36N R36E
¼ S 31
- 1965
- raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor.
- 45.34 The N. ¼ sec. cor. of sec. 6, hereinafter described.
- 80.52 The standard cor. of Tps. 35 and 36 N., Rs. 35 and 36 E., monumented with a squared willow stake, 1x1x24 ins., a portion of which is buried in the ground. No mkd. stone found.
- At the corner point
- Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.