

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 35 N., R. 36 E.

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T35N	R36E
S 26	S 25
S 35	S 36

1965

bury the iron rod alongside the iron post and raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

Land, gently rolling.

Soil, sandy clay.

Undergrowth, sagebrush.

From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of T. 35 N., R. 37 E., resurveyed concurrently under this same group.

N. $88^{\circ} 28'$ W., bet. secs. 25 and 36.

Over gently rolling land, along the general course of a rough bladed strip bearing E. and W., through medium low brush.

- 0.70 Wash, 30 lks. wide, 2 ft. deep, drains NE.
- 12.20 Wash, 20 lks. wide, 3 ft. deep, drains NE.
- 37.00 Wash, 20 lks. wide, 2 ft. deep, drains N.
- 38.20 Dim trail road, bears NE. and SW.
- 39.84 The $\frac{1}{4}$ sec. cor. of secs. 25 and 36, monumented with an iron pipe, 1 in. diam., 24 ins. long, exposed 8 ins. above the ground, and in a collar of limestone rock. This point is locally recognized as the true corner point and is accepted as the best remaining evidence of the position of the original corner. The cor. is situated in a bladed strip bearing E. and W.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T35N	R36E
$\frac{1}{4}$ S 25	
S 36	

1965

bury the iron pipe alongside the iron post and raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

N. $88^{\circ} 27'$ W., beginning new measurement.

Over level land, along a bladed strip.