

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 35 N., R. 36 E.

CHAINS

T35N	R36E
S 14	S 13
S 23	S 24

1965

bury the iron pipe and the pine post alongside the iron post and raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.

Land, gently rolling.
Soil, sandy clay to sand.
Undergrowth, sagebrush.

From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of T. 35 N., R. 37 E., resurveyed concurrently under this same group.

N. 89° 10' W., bet. secs. 13 and 24.

Over nearly level land, through medium dense low brush.

- 7.30 U. S. Highway Nos. 40 and 95, bears N. 67° 28' E. and S. 67° 28' W.
- 18.70 Trail road, bears ENE. and WSW.
- 25.70 Telephone line, bears N. 64° 19' E. and S. 64° 19' W.
- 33.80 Enter gently rolling low sand dunes, bearing N. and S.
- 40.14 Point for the ¼ sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T35N	R36E
¼ S 13	
¼ S 24	

1965

raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor.

- 80.28 The cor. of secs. 13, 14, 23 and 24.

Land, nearly level to gently rolling sand dunes.
Soil, sandy clay 1st. half; sand last half.
Undergrowth, sagebrush and shadscale.

N. 0° 12' E., bet. secs. 13 and 14.

Over gently rolling low sand dunes covered with brush.