

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 35 N., R. 36 E.

CHAINS		
59.20	Spur, slopes S.; desc. 10 ft. over gentle SW. slope.	
62.50	Lava rim rock bluff, 10 ft. high, bears SE. and NW.; desc. 290 ft. over SW. slope.	
81.29	<p>The cor. of secs. 2, 3, 10 and 11.</p> <p>Land, mountainous. Soil, sandy and rocky. Undergrowth, sagebrush and rabbit brush.</p>	
	<p>N. 1° 12' E., bet. secs. 2 and 3.</p> <p>Over rolling terrain, through medium undergrowth; asc. 30 ft. along gently rolling WSW. slope.</p>	
12.60	Top of ascent on W. slope; desc. 90 ft. along gently rolling WNW. slope.	
39.82	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T35N R36E $\frac{1}{4}$ S 3 S 2 1965</p> <p>raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Desc. 180 ft. over gently rolling NW. slope.</p>	
79.57	<p>Intersect the Seventh Standard Parallel North.</p> <p>Point for the closing cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T36N R36E S 34 S 3 S 2 CC T35N 1965</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor. from this corner</p> <p>The standard cor. of secs. 34 and 35, T. 36 N., R. 36 E., bears N. 89° 49' E., 4.98 chs. dist.</p>	