

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 35 N., R. 36 E.

CHAINS

N. $1^{\circ} 44'$ E., bet. secs. 3 and 4.

Over very gently rolling land, through medium dense low brush.

39.94 Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T35N R36E

S 4 | $\frac{1}{4}$ S 3

1965

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

50.00 Leave brush bearing E. and W., enter low rolling sand dunes.

61.30 Natural gas line access road, parallels gas line.

61.50 Natural gas line, buried, bears N. 45° E. and S. 45° W.

62.90 Leave rolling sand dunes, enter sagebrush bearing E. and W.

79.91 Intersect the Seventh Standard Parallel North.

Point for the closing cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T36N R36E

S 33
S 4 | S 3

CC

T35N

1965

raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, S. of cor.

from this corner

The standard cor. of secs. 33 and 34, T. 36 N., R. 36 E., bears N. $89^{\circ} 54'$ E., 5.13 chs. dist.

The standard $\frac{1}{4}$ sec. cor. of sec. 33, T. 36 N., R. 36 E., bears S. $89^{\circ} 54'$ W., 35.13 chs. dist.

Land, gently rolling.

Soil, sand to sandy clay.

Undergrowth, sagebrush and sparse native grasses.