DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 35 N., R. 36 E.

CHAINS	
39.86	Point for the ¼ sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. T35N R36E ¼ S 4 S 9 1965 raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor. Continue over gently rolling land; desc. 20 ft. over W. slope to sec. cor.
59.80	Natural gas line access road, parallels gas line.
60.10	Natural gas line, buried, bears N. 45° E. and S. 45° W.
79.72	The cor. of secs. 4, 5, 8 and 9. Land, gently rolling. Soil, sandy clay. Undergrowth, sagebrush and sparse native grasses.
	N. 1° 07' E., bet. secs. 4 and 5. Over gently rolling land, through medium dense low brush.
18.50	Trail road, bears ENE. and WSW.
32.00	Base of a low rolling ridge, bears E. and W.; asc. 20 ft. over S. slope.
40.43	Point for the ¼ sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. T35N R36E ¼ S 5 | S 4 1965 raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor. Asc. 80 ft. over gently rolling S. slope.
57.80	Crest of low sand ridge, bears E. and W.; desc. 20 ft. over NNW. slope.
69.60	Shallow swale, drains WSW.; asc. 20 ft. over S. slope.
80.80	Intersect the Seventh Standard Parallel North. Point for the closing sec. cor. of secs. 4 and 5.