

DEPENDENT RESURVEY, T. 34 N. R. 37 E.

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T34N	R37E
<u>S 26</u>	<u>S 25</u>
S 35	S 36

1965

raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

Land, nearly level.
Soil, sandy clay.
Undergrowth, greasewood.

From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of T. 34 N., R. 38 E., resurveyed concurrently under this same group.

N. $88^{\circ} 51'$ W., bet. secs. 25 and 36.

Over nearly level land, through low brush.

- 10.30 Small drainage, drains WSW.; leave rabbit brush, enter greasewood.
- 23.30 Wash, 10 lks. wide, 3 ft. deep, drains SW.
- 40.28 Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
- | | |
|---------------------------|------|
| T34N | R37E |
| $\frac{1}{4}$ <u>S 25</u> | |
| S 36 | |
- 1965
- raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of cor.
- 40.50 Small drainage, drains SW.
- 56.20 Wash, 10 lks. wide, 1 ft. deep, drains WSW.
- 77.80 Bladed dirt road, bears N. 1° E. and S. 1° W.
- 78.30 Fence, parallel to road.
- 80.20 Power line, parallel to road.