

DEPENDENT RESURVEY, T. 34 N., R. 37 E.

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. below the surface of the road, with brass cap mkd.

T34N	R37E
S 23	S 24
S 26	S 25

1965

from which

An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground and in a collar of stone, for a reference monument, bears N. 45° E., 66.0 ft. dist., with brass cap mkd. T34N R37E S 24 RM 66.0 ft. 1965, and an arrow pointing to the true corner point.

An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground and in a collar of stone, for a reference monument, bears S. 45° E., 66.0 ft. dist., with brass cap mkd. T34N R37E S 25 RM 66.0 ft., 1965, and an arrow pointing to the true corner point.

Bury the wooden hub alongside the iron post.

Land, nearly level.

Soil, sandy clay.

Undergrowth, sagebrush and rabbit brush.

From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of T. 34 N., R. 38 E., resurveyed concurrently under this same group.

N. 85° 58' W., bet. secs. 24 and 25.

Over nearly level desert land, through low brush.

24.30 Small drainage, drains WSW.

32.90 Power line, bears N. 89° E. and S. 89° W.

38.71 The ¼ sec. cor. of secs. 24 and 25, monumented with an iron rod, ½ in. diam., 12 ins. long, exposed 4 ins. above the ground; with the remains of the original corner monument, a badly deteriorated cottonwood stake, buried alongside the iron rod.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T34N	R37E
¼ S	S 24
	S 25

1965