

DEPENDENT RESURVEY, T. 34 N., R. 37 E.

CHAINS

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. below the surface of the road, with brass cap mkd.

T34N	R37E
S 14	S 13
S 23	S 24

1965

from which

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 22 ins. in the ground and in a collar of stone, for a reference monument, bears N. 45° E., 66.0 ft. dist., with brass cap mkd. T. 34 N., R. 37 E. S 13 RM 66.0 ft. 1965, with an arrow pointing to the true corner point.

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 22 ins. in the ground and in a collar of stone, for a reference monument, bears S. 45° E., 66.0 ft. dist., with brass cap mkd. T. 34 N., R. 37 E. S 24 RM 66.0 ft. 1965, with an arrow pointing to the true corner point.

Bury the iron pipe alongside the iron post.

Land, nearly level.
Soil, sandy clay.
Undergrowth, sagebrush.

From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of T. 34 N., R. 38 E., resurveyed concurrently under this same group.

N. $88^\circ 40'$ W., bet. secs. 13 and 24.

Over a very gentle W. slope, through low brush, along a bladed strip.

39.38

Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T34N	R37E
$\frac{1}{4}$ S 13	
S 24	

1965

raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.