

DEPENDENT RESURVEY, T. 34 N., R. 37 E.

CHAINS		
	<p style="text-align: center;">T34N R37E $\frac{1}{4}$ S 11 S 12 1965</p> <p>raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.</p>	
62.30	Leave dense brush, bearing generally E. and W.; enter scattered brush and salt grass.	
78.88	<p>The cor. of secs. 1, 2, 11 and 12, monumented with an iron pipe, 1 in. diam., 24 ins. long, exposed 4 ins. above ground level, at the junction of trail road, bearing E. and W. and a rough bladed strip bearing S. Locally recognized as the true corner point and is accepted as the best remaining evidence of the position of the original corner. The corner is S. of the traveled portion of the trail road, bearing E. and W.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T34N R37E S 2 S 1 S 11 S 12 1965</p> <p>bury the iron pipe alongside the iron post and raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.</p> <p>Land, nearly level. Soil, alkaline clay. Undergrowth, sagebrush, greasewood, rabbit brush and salt grass.</p>	
	<p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of T. 34 N., R. 38 E., resurveyed concurrently under this same group.</p> <p>N. 89° 47' W., bet. secs. 1 and 12.</p> <p>Over nearly level land, draining W., through low greasewood.</p>	
17.90	Wash, 10 lks. wide, 1 ft. deep, drains WNW.	
32.00	Enter rabbit brush, bearing N. and S.	
40.39	Point for the ¼ sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.	