

DEPENDENT RESURVEY, SOUTH BOUNDARY, T. 35 N., R. 37 E.

CHAINS

N. 89° 57' W., beginning new measurement.

Over gently rolling land; asc. 20 ft. over an E. slope.

5.00 Desc. 30 ft. along a N. slope.

15.40 Wash, 10 lks. wide, 2 ft. deep, drains N.

23.60 Ravine, drains NNE.; asc. 120 ft. over an E. slope to sec. cor.

35.00 Ravine, drains NE.

40.12 The cor. of secs. 5, 6, 31 and 32, monumented with a wooden post, 4x4x22 ins. long, loosely set in a mound of earth.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T35N	R37E
S 31	S 32
S 6	S 5
T34N	

1965

reset the wooden post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, gently rolling.

Soil, sandy loam.

Undergrowth, shadscale and sagebrush.

N. 89° 46' W., bet. secs. 6 and 31.

Over gently rolling land, along bladed strip; asc. 60 ft. to ¼ sec. cor.

12.80 Trail road, bears N. and S.

19.80 Bladed strip, bears N.

26.80 Ravine, drains N.

37.70 Ravine, drains NNE.

39.38 The ¼ sec. cor. of secs. 6 and 31, monumented with a steel pin, 24 ins. long, ¼ in. diam. This position is harmoniously related to existing original corners, has long been recognized as the cor. by adjacent land owners and is accepted as the best existing evidence of the position of the original corner.

At the corner point