

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 35 N., R. 37 E.

CHAINS	
	<p>Land, nearly level. Soil, sandy loam. Undergrowth, sagebrush and rabbitbrush.</p>
	<p>N. 0° 13' W., bet. secs. 3 and 4.</p> <p>Over nearly level land, through meadow land, along a fence.</p>
4.90	Corner of fences, bears N., S. and WSW.
6.00	Left bank of Humboldt River, course W.
7.20	Right bank of Humboldt River. Thence over sloughs.
31.10	Corner of fences bearing N., S. and ENE.
38.56	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4, determined latitudinally at proportionate measurement and longitudinally on a fence bearing N. and S.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground and in a collar of stone, with brass cap mkd.</p>
	<p>T35N R37E</p> <p style="margin-left: 40px;">$\frac{1}{4}$</p> <p style="margin-left: 40px;">S 4 S 3</p> <p>1965</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>N. 0° 03' E., beginning new measurement.</p> <p>Over nearly level marshy slough land, along a fence.</p>
21.60	Corner of fences, bearing S. and irregular E. and W.
39.81	Intersect the Seventh Standard Parallel North.
	<p>Point for the closing cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p>T36N R37E</p> <p style="margin-left: 40px;">S 33</p> <hr style="width: 20%; margin: 0 auto;"/> <p style="margin-left: 40px;">S 4 S 3</p> <p style="margin-left: 40px;">CC</p> <p style="margin-left: 40px;">T35N</p> <p>1965</p>
	<p>raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.</p>