

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 35 N., R. 37 E.

CHAINS
80.16

Intersect the Seventh Standard Parallel North.

Point for the closing cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T36N R37E

S 31

S 6 | S 5

CC

T35N

1965

raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From the point of intersection, the standard cor. of secs. 31 and 32, T. 36 N., R. 37 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of the resurvey of T. 36 N., R. 37 E., executed concurrently under this same group, bears N. $89^{\circ} 58'$ E., 7.34 chs. dist.

Land, gently rolling to nearly level.
Soil, sandy to sandy loam.
Undergrowth, sagebrush.

The point for the N. $\frac{1}{4}$ sec. cor. of sec. 5, on the Seventh Standard Parallel North and at midpoint on the N. bdy. of sec. 5.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T36N R37E

$\frac{1}{4}$ S 5

T35N

1965

raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From the cor. the standard $\frac{1}{4}$ sec. cor. of sec. 32, monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of the resurvey of T. 36 N., R. 37 E., executed concurrently under this same group, bears N. $89^{\circ} 58'$ E., 7.94 chs. dist.

The point for the N. $\frac{1}{4}$ sec. cor. of sec. 6, on the Seventh Standard Parallel North and at proportionate distance on the N. bdy. of sec. 6